


KEEFE PROPERTY TRACT 2 & 3

Detention Calculations

LIBERTY WAY

WEST CHESTER TOWNSHIP, BUTLER COUNTY, OHIO

As-Built 03-16-17



PREPARED BY:

BAYER BECKER

6900 TYLERSVILLE ROAD

MASON, OHIO 45040

P (513) 336-6600

SUMMARY OF DATA

Method of Hydrograph Development: TR-55

Software: Autodesk Storm and Sanitary Stand Alone

Site Stormwater Summary

Critical Storm = 50yr

See Previous Keefe Detention Reports

| Drainage Area Descriptions | Drainage Area (Acres) | CN | Tc (Mins) | Q1 (cfs) | Q1 (Cu. Ft.) | Q10 (cfs) | Q50 (cfs) |
|--|--------------------------|------|--------------|-------------|-----------------|--------------|--------------|
| On-Site Pre-Dev Areas | | | | | | | |
| Previously Detained Areas | 44.88 | 71.0 | 13.80 | 15.70 | | 71.24 | 123.57 |
| 16.4 + 4.3+18.3+5.9 = 44.90 (rounding error) | | | | | | | |
| New Commercial | 7.66 | 71.0 | 13.80 | 2.68 | Pg 7 9,724 | 12.64 | 21.19 |
| New Residential | 5.23 | 71.0 | 13.80 | 1.83 | Pg 8 6,647 | 8.63 | 14.44 |
| On-Site Post Developed to Basin | | | | | | | |
| Weatherington Pointe Cabelas & Outlots | 18.30 | 94.0 | 12.00 | 37.48 | | 73.47 | 100.72 |
| Tylers Place Blvd to Pond | 4.30 | 90.0 | 12.00 | 7.19 | | 15.69 | 22.18 |
| Keefe Tract 2 to Basin | 5.90 | 94.0 | 12.00 | 12.08 | | 24.15 | 32.49 |
| Weatherington Residential | 16.40 | 74.0 | 13.80 | 8.09 | | 30.84 | 52.33 |
| New Commerical | 7.02 | 96.0 | 12.00 | 15.62 | Pg 13 45,136 | 29.26 | 39.54 |
| Off-Site Areas | | | | | | | |
| Golf Course | 41.60 | 77.0 | 22.20 | 21.29 | | 73.09 | 119.72 |
| Liberty Way | 6.50 | 90.0 | 11.00 | 10.87 | | 23.73 | 33.53 |
| Bypass Areas | | | | | | | |
| New Commerical | 0.57 | 95.0 | 10.00 | 1.26 | Pg 14 3,454 | 2.40 | 3.25 |
| New Residential | 5.21 | 81.0 | 12.00 | 5.02 | Pg 15 13,889 | 14.41 | 22.23 |

Pg 9
Pg 10
Pg 11
Pg 12
Pg 18
Pg 16
Pg 17
Pg 19
Pg 21

| | |
|---|-------------------|
| Allowable Release Rate= | |
| Q1 On-Site Pre Developed + Q10 Previously Detained + Q50 Offsite | 223.27 CFS |

Note: CN for pre-developed conditions are based on previously developed and approved stormwater calculations for the Keefe Property. These numbers were based on a composite of B and C soils with open space in fair condition

See Page 30 for routed flow rates



Storm Water Detention/Retention Summary

Date: 9/21/2016 Revised: _____
 Design By: MJL Revised: _____
 Checked By: MJL Revised: 3/16/2017

Project: Keefe Tract 2 File No.: 15M053-000
 County: Butler City/Township: West Chester Twp

Basin Primary Basin

On-Site Area 29.32 Acres
 Off-Site Area 41.60 Acres
 Bypass Area 5.78 Acres

| Primary Basin | | |
|---------------|-------|----------|
| Orifice | Size | Inv Elev |
| Spillway | 60' | 862.54 |
| 1 | 16' | 860.50 |
| 1 | 66" ø | 854.43 |
| 1 | 6" ø | 852.10 |

Primary Basin

| A Event | B Inflow | C Outflow | D Elev | E Storage | F Com Byp | G Res Byp | =F+G Bypass | =C+F+G Total | Allowable |
|------------------|-------------|--------------|-----------|--------------|--------------|--------------|----------------|-----------------|--------------|
| Q ₁ | 79.90 | 16.67 | 855.43 | 144,335 | 1.27 | 5.09 | 6.36 | 23.03 | |
| Q ₁₀ | 203.64 | 105.33 | 858.07 | 281,247 | 2.44 | 14.42 | 16.86 | 122.19 | |
| Q ₅₀ | 296.85 | 173.75 | 859.71 | 369,687 | 3.25 Pg 19 | 22.23 Pg 21 | 25.48 | 199.23 | 223.27 Pg 30 |
| Q ₁₀₀ | 329.42 | 204.53 | 860.18 | 396,530 | 3.56 Pg 26 | 25.11 Pg 27 | 28.67 | 233.20 | 325.08 Pg 31 |

Basin Existing Pond

On-Site Area 4.30 Acres
 Off-Site Area 0.00 Acres
 Bypass Area 0.00 Acres

| Existing Pond | | |
|---------------|---------|----------|
| Orifice | Size | Inv Elev |
| T/GR | 8' | 867.30 |
| Spillway | 35' | 866.80 |
| 3 | 12"X36" | 865.50 |

| A Event | B Inflow | C Outflow | D Elev | E Storage |
|------------------|-------------|--------------|-----------|--------------|
| Q ₁ | 17.85 | 10.73 | 864.98 | 10,583 |
| Q ₁₀ | 52.24 | 36.79 | 865.67 | 26,321 |
| Q ₅₀ | 63.93 | 41.16 | 866.25 | 42,017 |
| Q ₁₀₀ | 67.81 | 42.67 | 866.53 | 49,766 |



Storm Water Detention/Retention Summary

Date: 9/9/2016 Revised: _____
 Design By: MJL Revised: _____
 Checked By: _____ Revised: _____

Project: Keefe Tract 2 File No.: 15M053-000
 County: Butler City/Township: West Chester Twp

Basin Cabelas WQ Basin

On-Site Area 18.30 Acres
 Off-Site Area 6.50 Acres
 Bypass Area 0.00 Acres


| Cabelas WQ | | |
|------------|---------|----------|
| Orifice | Size | Inv Elev |
| T/Dike | | 871.00 |
| South | 8' | 869.17 |
| North | 16' | 868.92 |
| 1 | 3.75" ø | 866.97 |

| A | B | C | D | E |
|------------------|----------|----------|----------|----------|
| Event | Inflow | Outflow | Elev | Storage |
| Q ₁ | 48.15 | 43.28 | 869.72 | 80,402 |
| Q ₁₀ | 97.12 | 84.16 | 870.48 | 91,769 |
| Q ₅₀ | 134.06 | 102.19 | 871.41 | 107,120 |
| Q ₁₀₀ | 146.85 | 108.61 | 871.84 | 114,387 |

Previously Detained Areas

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 71.24 |
| Storm Frequency | = | 10 yrs | Time to Peak = | 14:36 |
| Time Interval | = | 6 min | Hyd. Volume = | 216,358 Ft ³ |
| Drainage Area | = | 44.88 Acres | Curve Number = | 71 |
| Tc Method | = | User | Time of conc. (Tc) = | 13.80 Mins |
| Total precip. | = | 3.9 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Predeveloped Commercial Areas

| | | | | |
|-----------------|---|--------------------|----------------------|-----------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 2.68 |
| Storm Frequency | = | 1 yrs | Time to Peak = | 14:36 |
| Time Interval | = | 6 min | Hyd. Volume = | 9,724 Ft ³ |
| Drainage Area | = | 7.66 Acres | Curve Number = | 71 |
| Tc Method | = | User | Time of conc. (Tc) = | 13.80 Mins |
| Total precip. | = | 2.4 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Predeveloped Residential Area

| | | | | |
|-----------------|---|--------------------|----------------------|-----------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 1.83 |
| Storm Frequency | = | 1 yrs | Time to Peak = | 14:36 |
| Time Interval | = | 6 min | Hyd. Volume = | 6,647 Ft ³ |
| Drainage Area | = | 5.23 Acres | Curve Number = | 71 |
| Tc Method | = | User | Time of conc. (Tc) = | 13.80 Mins |
| Total precip. | = | 2.4 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Weatherington Pointe Cabelas & Outlots

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 100.72 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 299,066 Ft ³ |
| Drainage Area | = | 18.30 Acres | Curve Number = | 94 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 5.2 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Tylers Place Blvd to Pond

| | | | | |
|-----------------|---|--------------------|----------------------|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 22.18 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 63,568 Ft ³ |
| Drainage Area | = | 4.30 Acres | Curve Number = | 90 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 5.2 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Keefe Tract 2 to Basin

| | | | | |
|-----------------|---|--------------------|----------------------|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 32.49 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 96,465 Ft ³ |
| Drainage Area | = | 5.90 Acres | Curve Number = | 94 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 5.2 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Weatherington Residential

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 52.33 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 150,217 Ft ³ |
| Drainage Area | = | 16.40 Acres | Curve Number = | 74 |
| Tc Method | = | User | Time of conc. (Tc) = | 13.80 Mins |
| Total precip. | = | 5.2 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Commerical to Basin

| | | | | |
|-----------------|---|--------------------|----------------------|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 15.62 |
| Storm Frequency | = | 1 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 45,136 Ft ³ |
| Drainage Area | = | 6.86 Acres | Curve Number = | 96 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 2.4 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Commercial to Bypass

| | | | | |
|-----------------|---|--------------------|----------------------|-----------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 1.26 |
| Storm Frequency | = | 1 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 3.454 Ft ³ |
| Drainage Area | = | 0.80 Acres | Curve Number = | 95 |
| Tc Method | = | User | Time of conc. (Tc) = | 10.00 Mins |
| Total precip. | = | 2.4 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Residential

| | | | | | |
|-----------------|---|--------------------|--------------------|---|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge | = | 5.02 |
| Storm Frequency | = | 1 yrs | Time to Peak | = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume | = | 13,889 Ft ³ |
| Drainage Area | = | 5.23 Acres | Curve Number | = | 81 |
| Tc Method | = | User | Time of conc. (Tc) | = | 10.00 Mins |
| Total precip. | = | 2.4 in | Date | = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | | |


Notes:



Liberty Way Off-Site

| | | | | |
|-----------------|---|--------------------|----------------------|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 33.53 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 96,034 Ft ³ |
| Drainage Area | = | 6.50 Acres | Curve Number = | 90 |
| Tc Method | = | User | Time of conc. (Tc) = | 11.00 Mins |
| Total precip. | = | 5.20 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Golf Course - Off Site

| | | | | | |
|-----------------|---|--------------------|--------------------|---|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge | = | 119.72 |
| Storm Frequency | = | 50 yrs | Time to Peak | = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume | = | 421,422 Ft ³ |
| Drainage Area | = | 41.60 Acres | Curve Number | = | 77 |
| Tc Method | = | User | Time of conc. (Tc) | = | 22.20 Mins |
| Total precip. | = | 5.2 in | Date | = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | | |


Notes:



Postdeveloped New Commercial

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 39.54 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 120,512 Ft ³ |
| Drainage Area | = | 6.86 Acres | Curve Number = | 96 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 5.2 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Commercial to Bypass

| | | | | |
|-----------------|---|--------------------|----------------------|-----------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 3.25 |
| Storm Frequency | = | 50 yrs | Time to Peak = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 9,544 Ft ³ |
| Drainage Area | = | 0.80 Acres | Curve Number = | 95 |
| Tc Method | = | User | Time of conc. (Tc) = | 10.00 Mins |
| Total precip. | = | 5.2 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Residential

| | | | | | |
|-----------------|---|--------------------|--------------------|---|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge | = | 22.23 |
| Storm Frequency | = | 50 yrs | Time to Peak | = | 14:30 |
| Time Interval | = | 6 min | Hyd. Volume | = | 59,816 Ft ³ |
| Drainage Area | = | 5.23 Acres | Curve Number | = | 81 |
| Tc Method | = | User | Time of conc. (Tc) | = | 11.00 Mins |
| Total precip. | = | 5.2 in | Date | = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | | |


Notes:



Weatherington Pointe Cabelas and Outlots

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 110.43 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 329,991 Ft ³ |
| Drainage Area | = | 18.30 Acres | Curve Number = | 94 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 5.67 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Tylers Place Blvd to Pond

| | | | | | |
|-----------------|---|--------------------|--------------------|---|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge | = | 24.52 |
| Storm Frequency | = | 100 yrs | Time to Peak | = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume | = | 70,708 Ft ³ |
| Drainage Area | = | 4.30 Acres | Curve Number | = | 90 |
| Tc Method | = | User | Time of conc. (Tc) | = | 12.00 Mins |
| Total precip. | = | 5.67 in | Date | = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | | |


Notes:



Keefe Tract 2 to Basin

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 35.6 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 106,363 Ft ³ |
| Drainage Area | = | 5.90 Acres | Curve Number = | 94 |
| Tc Method | = | User | Time of conc. (Tc) = | 12.00 Mins |
| Total precip. | = | 5.67 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Weatherington Residential

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 60.54 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 173,243 Ft ³ |
| Drainage Area | = | 16.40 Acres | Curve Number = | 74 |
| Tc Method | = | User | Time of conc. (Tc) = | 13.80 Mins |
| Total precip. | = | 5.67 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Commercial to Basin

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 43.22 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 132,674 Ft ³ |
| Drainage Area | = | 6.86 Acres | Curve Number = | 96 |
| Tc Method | = | User | Time of conc. (Tc) = | 13.80 Mins |
| Total precip. | = | 5.67 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Commercial to Bypass

| | | | | |
|-----------------|---|--------------------|----------------------|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 3.56 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 10,517 Ft ³ |
| Drainage Area | = | 0.80 Acres | Curve Number = | 95 |
| Tc Method | = | User | Time of conc. (Tc) = | 10.00 Mins |
| Total precip. | = | 5.67 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Postdeveloped New Residential

| | | | | |
|-----------------|---|--------------------|----------------------|------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 25.11 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 67,792 Ft ³ |
| Drainage Area | = | 5.23 Acres | Curve Number = | 81 |
| Tc Method | = | User | Time of conc. (Tc) = | 10.00 Mins |
| Total precip. | = | 5.67 in | Date = | 9/8/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Liberty Way Off-Site

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 37.07 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 106,730 Ft ³ |
| Drainage Area | = | 6.50 Acres | Curve Number = | 90 |
| Tc Method | = | User | Time of conc. (Tc) = | 11.00 Mins |
| Total precip. | = | 5.67 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Golf Course - Off Site

| | | | | |
|-----------------|---|--------------------|----------------------|-------------------------|
| Hydrograph Type | = | SCS Runoff Type II | Peak Discharge = | 137.07 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:30 |
| Time Interval | = | 6 min | Hyd. Volume = | 482,093 Ft ³ |
| Drainage Area | = | 41.60 Acres | Curve Number = | 77 |
| Tc Method | = | User | Time of conc. (Tc) = | 22.20 Mins |
| Total precip. | = | 5.67 in | Date = | 6/2/2016 |
| Storm Duration | = | 24 hrs | | |


Notes:



Allowable Release Rate Hydrograph

Method of Hydrograph Development: TR-55

Software: Autodesk Storm and Sanitary Stand Alone




| | | | |
|---------------|--------------------|---------------|------------------|
| Peak | | | |
| 1yr Pre Dev | 4.51 cfs Pg7 + Pg8 | 50yr Golf | 119.72 cfs Pg 16 |
| 10yr Ex Basin | 71.24 cfs Pg 6 | 50yr Lib Way | 33.53 cfs Pg 17 |
| | | 50yr Allowabl | 223.27 cfs |

Allowable Release Rate Hydrograph

Method of Hydrograph Development: TR-55

Software: Autodesk Storm and Sanitary Stand Alone



| Peak | | | |
|---------------|------------|---------------|------------|
| 50yr Pre Dev | 35.63 cfs | 100yr Golf | 137.07 cfs |
| 50yr Ex Basin | 123.57 cfs | 100yr Lib Way | 37.07 cfs |
| | | 100yr Allowat | 325.08 cfs |



Water Quality Volume

Project: Keefe Tracts 2 & 3
Job No.: 15M053-000
Basin ID: Primary Basin

Designed By: MJL
Checked By: ASB
Revised By:

Date: 9/13/16
Date: 3/16/17
Date:

Required Water Quality Volume

$$WQ_v = P C A/12$$

Site Drainage Area (A) = 81.56 acres (To Basin)
Rainfall Depth (P) = 0.75 in.
Runoff Coefficient (C) = 0.46

WQ_v = 2.368 acre-ft.
103,150 cu.ft.

Residential Area (A) = 16.40 acres
Residential (C) = 0.40
Commercial Area (A) = 23.56 acres
Commercial (C) = 0.80
Golf Course Area (A) = 41.60 acres
Golf Course (C) = 0.30

75% Wet Pond 1.78 acre-ft.
77,363 cu.ft.

Water Quality Release Rate

$$Q_{wqv} = \text{Total WQ}_v / \text{RT}$$

Retention Time (RT) = 24 hours

Q_{wqv} = 0.90 cfs

Provided Retention Time = 33.92 Hours

Water Quality Outlet Orifice

Contour Areas

| | Elevation ft | Area ft ² | Volume ft ³ | Cum. Vol. ft ³ | Elevation at V | Storage at Elev |
|--------------|-----------------|-------------------------|---------------------------|------------------------------|-------------------|--------------------|
| Basin Inv. = | 844.00 | 8608.90 | 0.00 | 0.00 | | |
| Contour 1 = | 845.00 | 10164.05 | 9386.48 | 9386.48 | | |
| Contour 2 = | 846.00 | 11827.50 | 10995.78 | 20382.25 | | |
| Contour 3 = | 847.00 | 13596.40 | 12711.95 | 33094.20 | | |
| Contour 4 = | 848.00 | 15472.65 | 14534.53 | 47628.73 | | |
| Contour 5 = | 849.00 | 17455.30 | 16463.98 | 64092.70 | | |
| Contour 6 = | 850.00 | 19545.30 | 18500.30 | 82593.00 | 849.72 | |
| Contour 7 = | 851.00 | 29644.75 | 24595.03 | 107188.03 | | |
| Contour 8 = | 852.00 | 44649.05 | 37146.90 | 144334.93 | | |
| Contour 9 = | 852.50 | 47003.00 | 57485.81 | 0.00 | | |
| Contour 10 = | 853.00 | 48279.00 | 23820.50 | 23820.50 | | |
| Contour 11 = | 854.00 | 49398.00 | 48838.50 | 72659.00 | | |
| Contour 12 = | 855.00 | 50343.00 | 49870.50 | 122529.50 | 854.09 | 109345.58 |
| Contour 13 = | 856.00 | 51255.00 | 50799.00 | 173328.50 | | |
| Contour 14 = | 857.00 | 52205.00 | 51730.00 | 225058.50 | | |
| Contour 15 = | 858.00 | 53176.00 | 52690.50 | 277749.00 | | |
| Contour 16 = | 859.00 | 54341.00 | 53758.50 | 331507.50 | | |
| Contour 17 = | 860.00 | 55910.00 | 55125.50 | 386633.00 | | |
| Contour 18 = | 861.00 | 55910.00 | 55910.00 | 442543.00 | | |
| Contour 19 = | 862.00 | 55910.00 | 55910.00 | 498453.00 | | |
| Contour 20 = | 863.00 | 55910.00 | 55910.00 | 554363.00 | | |

$$Q = N C_d A_o (2 g \Delta h)^{1/2}$$

$$C_d = 0.61$$

$$A_o = \pi D^2/4 \text{ for circular orifices; } = h * w \text{ for rectangular orifices}$$

$$g = 32.20 \text{ ft/sec}^2$$

$$Q = Q_{wqv} = 0.895 \text{ cfs}$$

Required Volume = V = 77363 ft³
Elevation at V = 854.09

Number of orifices = N = 1

$$\text{Orifice } h = 6.000 \text{ inch}$$

$$\text{Orifice } w = 0.00 \text{ inch (} = 0 \text{ for circular orifice)}$$

$$\Delta h_{\min}^{\text{avg}} = (\text{Elev at V} - \text{Basin Inv})/2 - 1/2 h = 4.80 \text{ ft}$$

$$A_{\text{trial}} = Q / (N C_d (2 g \Delta h_{\min}^{\text{avg}})^{1/2}) = 12.03 \text{ in}^2$$

$$\text{Actual } A = A_o = 28.27 \text{ in}^2$$

$$\Delta h^{\text{avg}} = (Q / (N C_d A_o))^2 / (2 g) = 0.87 \text{ ft}$$

Elev = 854.74 > Elevation at V = 854.09 Good

Storage = 109345.58 ft³ Q = 0.895 cfs



Water Quality Volume

| | | | | | |
|-----------|--------------------|--------------|-----|-------|--------|
| Project: | Keefe Tracts 2 & 3 | Designed By: | MJL | Date: | 6/2/16 |
| Job No.: | 15M053-000 | Checked By: | | Date: | |
| Basin ID: | Residential | Revised By: | | Date: | |

Required Water Quality Volume

$$WQ_v = P C A / 12$$

Site Drainage Area (A) = 5.23 acres (To Basin)

Rainfall Depth (P) = 0.75 in.

Impervious Area = 2.81 acres

i = 0.54

Runoff Coefficient (C) = 0.36

$$C = 0.858i^3 - 0.78i^2 + 0.774i + 0.04$$

WQ_v = 0.119 acre-ft.
5,180 cu.ft.

20% Sediment 1,036 cu.ft.
Total WQ= 6,215 cu.ft.

Residential Water Quality Volume and Release Rates will be provided per each building in underground storage at building permits

Pond Report

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2016 by Autodesk, Inc. v10.5

Tuesday, 07 / 26 / 2016

Pond No. 2 - Existing Pond

Pond Data

Contours -User-defined contour areas. Conic method used for volume calculation. Begining Elevation = 853.10 ft

Stage / Storage Table

| Stage (ft) | Elevation (ft) | Contour area (sqft) | Incr. Storage (cuft) | Total storage (cuft) |
|------------|----------------|---------------------|----------------------|----------------------|
| 0.00 | 853.10 | 00 | 0 | 0 |
| 0.90 | 854.00 | 109 | 33 | 33 |
| 1.90 | 855.00 | 8,505 | 3,192 | 3,225 |
| 2.90 | 856.00 | 20,179 | 13,927 | 17,151 |
| 3.90 | 857.00 | 34,118 | 26,843 | 43,994 |
| 4.90 | 858.00 | 48,025 | 40,870 | 84,864 |
| 5.90 | 859.00 | 61,936 | 54,828 | 139,692 |
| 6.90 | 860.00 | 71,234 | 66,524 | 206,216 |
| 7.90 | 861.00 | 74,999 | 73,101 | 279,317 |

Culvert / Orifice Structures

| | [A] | [B] | [C] | [PrfRsr] |
|-----------------|----------|------|------|----------|
| Rise (in) | = 60.00 | 0.00 | 0.00 | 0.00 |
| Span (in) | = 60.00 | 0.00 | 0.00 | 0.00 |
| No. Barrels | = 1 | 0 | 0 | 0 |
| Invert El. (ft) | = 853.10 | 0.00 | 0.00 | 0.00 |
| Length (ft) | = 92.00 | 0.00 | 0.00 | 0.00 |
| Slope (%) | = 1.00 | 0.00 | 0.00 | n/a |
| N-Value | = .024 | .013 | .013 | n/a |
| Orifice Coeff. | = 0.60 | 0.60 | 0.60 | 0.60 |
| Multi-Stage | = n/a | No | No | No |

Weir Structures

| | [A] | [B] | [C] | [D] |
|----------------|-----------------------|------|------|------|
| Crest Len (ft) | = 0.00 | 0.00 | 0.00 | 0.00 |
| Crest El. (ft) | = 0.00 | 0.00 | 0.00 | 0.00 |
| Weir Coeff. | = 3.33 | 3.33 | 3.33 | 3.33 |
| Weir Type | = --- | --- | --- | --- |
| Multi-Stage | = No | No | No | No |
| Exfil.(in/hr) | = 0.000 (by Wet area) | | | |
| TW Elev. (ft) | = 0.00 | | | |

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).

Stage / Storage / Discharge Table

| Stage ft | Storage cuft | Elevation ft | Clv A cfs | Clv B cfs | Clv C cfs | PrfRsr cfs | Wr A cfs | Wr B cfs | Wr C cfs | Wr D cfs | Exfil cfs | User cfs | Total cfs |
|----------|--------------|--------------|-----------|-----------|-----------|------------|----------|----------|----------|----------|-----------|----------|-----------|
| 0.00 | 0 | 853.10 | 0.00 | --- | --- | --- | --- | --- | --- | --- | --- | --- | 0.000 |
| 0.09 | 3 | 853.19 | 0.08 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 0.077 |
| 0.18 | 7 | 853.28 | 0.33 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 0.329 |
| 0.27 | 10 | 853.37 | 0.73 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 0.731 |
| 0.36 | 13 | 853.46 | 1.29 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 1.288 |
| 0.45 | 16 | 853.55 | 2.01 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 2.015 |
| 0.54 | 20 | 853.64 | 2.87 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 2.875 |
| 0.63 | 23 | 853.73 | 3.90 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 3.896 |
| 0.72 | 26 | 853.82 | 5.04 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 5.041 |
| 0.81 | 29 | 853.91 | 6.35 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 6.346 |
| 0.90 | 33 | 854.00 | 7.77 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 7.768 |
| 1.00 | 352 | 854.10 | 9.55 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 9.547 |
| 1.10 | 671 | 854.20 | 11.46 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 11.46 |
| 1.20 | 990 | 854.30 | 13.52 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 13.52 |
| 1.30 | 1,309 | 854.40 | 15.79 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 15.79 |
| 1.40 | 1,629 | 854.50 | 18.13 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 18.13 |
| 1.50 | 1,948 | 854.60 | 20.66 ic | --- | --- | --- | --- | --- | --- | --- | --- | --- | 20.66 |
| 1.60 | 2,267 | 854.70 | 23.11 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 23.11 |
| 1.70 | 2,586 | 854.80 | 25.54 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 25.54 |
| 1.80 | 2,905 | 854.90 | 28.07 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 28.07 |
| 1.90 | 3,225 | 855.00 | 30.58 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 30.58 |
| 2.00 | 4,617 | 855.10 | 33.15 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 33.15 |
| 2.10 | 6,010 | 855.20 | 35.79 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 35.79 |
| 2.20 | 7,403 | 855.30 | 38.47 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 38.47 |
| 2.30 | 8,795 | 855.40 | 41.09 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 41.09 |
| 2.40 | 10,188 | 855.50 | 43.83 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 43.83 |
| 2.50 | 11,581 | 855.60 | 46.49 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 46.49 |
| 2.60 | 12,973 | 855.70 | 49.25 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 49.25 |
| 2.70 | 14,366 | 855.80 | 51.91 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 51.91 |
| 2.80 | 15,759 | 855.90 | 54.65 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 54.65 |
| 2.90 | 17,151 | 856.00 | 57.37 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 57.37 |
| 3.00 | 19,836 | 856.10 | 60.04 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 60.04 |
| 3.10 | 22,520 | 856.20 | 62.67 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 62.67 |
| 3.20 | 25,204 | 856.30 | 65.24 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 65.24 |

Continues on next page...

Existing Pond

Stage / Storage / Discharge Table

| Stage ft | Storage cuft | Elevation ft | Clv A cfs | Clv B cfs | Clv C cfs | PrfRsr cfs | Wr A cfs | Wr B cfs | Wr C cfs | Wr D cfs | Exfil cfs | User cfs | Total cfs |
|-------------|-----------------|-----------------|--------------|--------------|--------------|---------------|-------------|-------------|-------------|-------------|--------------|-------------|--------------|
| 3.30 | 27,888 | 856.40 | 67.84 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 67.84 |
| 3.40 | 30,573 | 856.50 | 70.35 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 70.35 |
| 3.50 | 33,257 | 856.60 | 72.77 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 72.77 |
| 3.60 | 35,941 | 856.70 | 75.26 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 75.26 |
| 3.70 | 38,625 | 856.80 | 77.54 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 77.54 |
| 3.80 | 41,310 | 856.90 | 79.84 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 79.84 |
| 3.90 | 43,994 | 857.00 | 81.99 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 81.99 |
| 4.00 | 48,081 | 857.10 | 84.04 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 84.04 |
| 4.10 | 52,168 | 857.20 | 86.03 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 86.03 |
| 4.20 | 56,255 | 857.30 | 87.87 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 87.87 |
| 4.30 | 60,342 | 857.40 | 89.53 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 89.53 |
| 4.40 | 64,429 | 857.50 | 91.07 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 91.07 |
| 4.50 | 68,516 | 857.60 | 92.42 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 92.42 |
| 4.60 | 72,603 | 857.70 | 93.53 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 93.53 |
| 4.70 | 76,690 | 857.80 | 94.39 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 94.39 |
| 4.80 | 80,777 | 857.90 | 94.90 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 94.90 |
| 4.90 | 84,864 | 858.00 | 94.87 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 94.87 |
| 5.00 | 90,347 | 858.10 | 92.96 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 92.96 |
| 5.10 | 95,829 | 858.20 | 97.89 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 97.89 |
| 5.20 | 101,312 | 858.30 | 102.57 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 102.57 |
| 5.30 | 106,795 | 858.40 | 107.05 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 107.05 |
| 5.40 | 112,278 | 858.50 | 111.35 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 111.35 |
| 5.50 | 117,760 | 858.60 | 115.49 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 115.49 |
| 5.60 | 123,243 | 858.70 | 119.49 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 119.49 |
| 5.70 | 128,726 | 858.80 | 123.36 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 123.36 |
| 5.80 | 134,209 | 858.90 | 127.11 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 127.11 |
| 5.90 | 139,692 | 859.00 | 130.76 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 130.76 |
| 6.00 | 146,344 | 859.10 | 134.30 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 134.30 |
| 6.10 | 152,996 | 859.20 | 137.75 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 137.75 |
| 6.20 | 159,649 | 859.30 | 141.12 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 141.12 |
| 6.30 | 166,301 | 859.40 | 144.41 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 144.41 |
| 6.40 | 172,954 | 859.50 | 147.62 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 147.62 |
| 6.50 | 179,606 | 859.60 | 150.77 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 150.77 |
| 6.60 | 186,258 | 859.70 | 153.85 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 153.85 |
| 6.70 | 192,911 | 859.80 | 156.88 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 156.88 |
| 6.80 | 199,563 | 859.90 | 159.84 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 159.84 |
| 6.90 | 206,216 | 860.00 | 162.76 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 162.76 |
| 7.00 | 213,526 | 860.10 | 165.62 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 165.62 |
| 7.10 | 220,836 | 860.20 | 168.43 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 168.43 |
| 7.20 | 228,146 | 860.30 | 171.20 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 171.20 |
| 7.30 | 235,456 | 860.40 | 173.92 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 173.92 |
| 7.40 | 242,766 | 860.50 | 176.60 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 176.60 |
| 7.50 | 250,076 | 860.60 | 179.24 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 179.24 |
| 7.60 | 257,386 | 860.70 | 181.84 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 181.84 |
| 7.70 | 264,697 | 860.80 | 184.40 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 184.40 |
| 7.80 | 272,007 | 860.90 | 186.93 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 186.93 |
| 7.90 | 279,317 | 861.00 | 189.43 oc | --- | --- | --- | --- | --- | --- | --- | --- | --- | 189.43 |

...End

Pond Report

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2016 by Autodesk, Inc. v10.514

Thursday, 03 / 16 / 2017

Pond No. 1 - Walled Pond

Pond Data

Contours -User-defined contour areas. Conic method used for volume calculation. Begining Elevation = 852.50 ft

Stage / Storage Table

| Stage (ft) | Elevation (ft) | Contour area (sqft) | Incr. Storage (cuft) | Total storage (cuft) |
|------------|----------------|---------------------|----------------------|----------------------|
| 0.00 | 852.50 | 47,003 | 0 | 0 |
| 0.50 | 853.00 | 48,279 | 23,817 | 23,817 |
| 1.50 | 854.00 | 49,398 | 48,833 | 72,650 |
| 2.50 | 855.00 | 50,343 | 49,865 | 122,515 |
| 3.50 | 856.00 | 51,255 | 50,793 | 173,308 |
| 4.50 | 857.00 | 52,205 | 51,724 | 225,032 |
| 5.50 | 858.00 | 53,176 | 52,685 | 277,717 |
| 6.50 | 859.00 | 54,341 | 53,752 | 331,469 |
| 7.50 | 860.00 | 55,910 | 55,118 | 386,587 |
| 8.50 | 861.00 | 55,910 | 55,904 | 442,491 |
| 9.50 | 862.00 | 55,910 | 55,904 | 498,396 |
| 10.50 | 863.00 | 55,910 | 55,904 | 554,300 |

Culvert / Orifice Structures

| | [A] | [B] | [C] | [PrfRsr] |
|-----------------|----------|--------|--------|----------|
| Rise (in) | = 48.00 | 6.00 | 66.00 | 0.00 |
| Span (in) | = 96.00 | 6.00 | 66.00 | 0.00 |
| No. Barrels | = 1 | 1 | 1 | 0 |
| Invert El. (ft) | = 852.10 | 852.10 | 854.43 | 0.00 |
| Length (ft) | = 277.00 | 0.00 | 0.00 | 0.00 |
| Slope (%) | = 0.26 | 0.00 | 0.00 | n/a |
| N-Value | = .015 | .015 | .015 | n/a |
| Orifice Coeff. | = 0.61 | 0.61 | 0.61 | 0.60 |
| Multi-Stage | = n/a | Yes | Yes | No |

Weir Structures

| | [A] | [B] | [C] | [D] |
|----------------|----------------------|--------|------|------|
| Crest Len (ft) | = 16.00 | 60.00 | 0.00 | 0.00 |
| Crest El. (ft) | = 860.50 | 862.54 | 0.00 | 0.00 |
| Weir Coeff. | = 3.33 | 2.60 | 3.33 | 3.33 |
| Weir Type | = 1 | Broad | --- | --- |
| Multi-Stage | = Yes | No | No | No |
| Exfil.(in/hr) | = 0.000 (by Contour) | | | |
| TW Elev. (ft) | = 0.00 | | | |

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).

Stage / Storage / Discharge Table

| Stage ft | Storage cuft | Elevation ft | Civ A cfs | Civ B cfs | Civ C cfs | PrfRsr cfs | Wr A cfs | Wr B cfs | Wr C cfs | Wr D cfs | Exfil cfs | User cfs | Total cfs |
|----------|--------------|--------------|-----------|-----------|-----------|------------|----------|----------|----------|----------|-----------|----------|-----------|
| 0.00 | 0 | 852.50 | 0.00 | 0.00 | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.000 |
| 0.05 | 2,382 | 852.55 | 7.05 ic | 0.21 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.206 |
| 0.10 | 4,763 | 852.60 | 7.05 ic | 0.31 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.306 |
| 0.15 | 7,145 | 852.65 | 7.05 ic | 0.37 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.375 |
| 0.20 | 9,527 | 852.70 | 7.05 ic | 0.43 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.433 |
| 0.25 | 11,909 | 852.75 | 7.05 ic | 0.48 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.484 |
| 0.30 | 14,290 | 852.80 | 7.05 ic | 0.53 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.530 |
| 0.35 | 16,672 | 852.85 | 7.05 ic | 0.57 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.572 |
| 0.40 | 19,054 | 852.90 | 7.05 ic | 0.61 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.612 |
| 0.45 | 21,436 | 852.95 | 7.05 ic | 0.65 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.649 |
| 0.50 | 23,817 | 853.00 | 7.05 ic | 0.68 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.684 |
| 0.60 | 28,701 | 853.10 | 7.05 ic | 0.75 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.749 |
| 0.70 | 33,584 | 853.20 | 7.05 ic | 0.81 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.809 |
| 0.80 | 38,467 | 853.30 | 7.05 ic | 0.87 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.865 |
| 0.90 | 43,350 | 853.40 | 7.05 ic | 0.92 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.918 |
| 1.00 | 48,234 | 853.50 | 7.05 ic | 0.97 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 0.967 |
| 1.10 | 53,117 | 853.60 | 7.05 ic | 1.01 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.015 |
| 1.20 | 58,000 | 853.70 | 7.05 ic | 1.06 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.060 |
| 1.30 | 62,883 | 853.80 | 7.05 ic | 1.10 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.103 |
| 1.40 | 67,767 | 853.90 | 7.05 ic | 1.14 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.145 |
| 1.50 | 72,650 | 854.00 | 7.05 ic | 1.18 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.185 |
| 1.60 | 77,636 | 854.10 | 7.05 ic | 1.22 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.224 |
| 1.70 | 82,623 | 854.20 | 7.05 ic | 1.26 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.261 |
| 1.80 | 87,609 | 854.30 | 7.05 ic | 1.30 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.298 |
| 1.90 | 92,596 | 854.40 | 7.05 ic | 1.33 ic | 0.00 | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.333 |
| 2.00 | 97,582 | 854.50 | 7.05 ic | 1.37 ic | 0.06 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.428 |
| 2.10 | 102,569 | 854.60 | 7.05 ic | 1.40 ic | 0.33 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 1.734 |
| 2.20 | 107,555 | 854.70 | 7.05 ic | 1.43 ic | 0.83 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 2.262 |
| 2.30 | 112,542 | 854.80 | 7.05 ic | 1.47 ic | 1.54 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 3.004 |
| 2.40 | 117,528 | 854.90 | 7.05 ic | 1.50 ic | 2.38 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 3.883 |
| 2.50 | 122,515 | 855.00 | 7.05 ic | 1.53 ic | 3.49 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 5.020 |

Continues on next page...

Stage / Storage / Discharge Table

| Stage ft | Storage cuft | Elevation ft | Clv A cfs | Clv B cfs | Clv C cfs | PrfRsr cfs | Wr A cfs | Wr B cfs | Wr C cfs | Wr D cfs | Exfil cfs | User cfs | Total cfs |
|-------------|-----------------|-----------------|--------------|--------------|--------------|---------------|-------------|-------------|-------------|-------------|--------------|-------------|--------------|
| 2.60 | 121,975 | 855.10 | 5.31 ic | 1.48 ic | 3.83 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 5.309 |
| 2.70 | 126,852 | 855.20 | 6.82 ic | 1.51 ic | 5.30 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 6.816 |
| 2.80 | 131,729 | 855.30 | 8.27 ic | 1.54 ic | 6.73 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 8.270 |
| 2.90 | 136,606 | 855.40 | 10.38 ic | 1.57 ic | 8.80 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 10.38 |
| 3.00 | 141,482 | 855.50 | 12.33 ic | 1.60 ic | 10.73 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 12.33 |
| 3.10 | 146,359 | 855.60 | 14.51 ic | 1.61 ic | 12.90 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 14.51 |
| 3.20 | 151,236 | 855.70 | 16.31 ic | 1.62 ic | 14.69 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 16.31 |
| 3.30 | 156,113 | 855.80 | 18.92 ic | 1.63 ic | 17.29 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 18.92 |
| 3.40 | 160,990 | 855.90 | 21.78 ic | 1.64 ic | 20.14 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 21.77 |
| 3.50 | 165,867 | 856.00 | 24.08 ic | 1.65 ic | 22.43 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 24.08 |
| 3.60 | 170,852 | 856.10 | 27.37 ic | 1.65 ic | 25.72 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 27.37 |
| 3.70 | 175,837 | 856.20 | 30.92 ic | 1.66 ic | 29.25 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 30.91 |
| 3.80 | 180,822 | 856.30 | 33.71 ic | 1.67 ic | 32.05 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 33.71 |
| 3.90 | 185,807 | 856.40 | 36.65 ic | 1.68 ic | 34.97 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 36.64 |
| 4.00 | 190,792 | 856.50 | 40.78 ic | 1.68 ic | 39.10 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 40.78 |
| 4.10 | 195,777 | 856.60 | 44.01 ic | 1.69 ic | 42.31 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 44.00 |
| 4.20 | 200,762 | 856.70 | 48.52 ic | 1.69 ic | 46.83 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 48.52 |
| 4.30 | 205,748 | 856.80 | 52.02 ic | 1.70 ic | 50.32 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 52.02 |
| 4.40 | 210,733 | 856.90 | 55.63 ic | 1.71 ic | 53.91 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 55.62 |
| 4.50 | 215,718 | 857.00 | 60.63 ic | 1.71 ic | 58.91 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 60.62 |
| 4.60 | 220,814 | 857.10 | 64.46 ic | 1.72 ic | 62.74 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 64.46 |
| 4.70 | 225,909 | 857.20 | 68.38 ic | 1.73 ic | 66.65 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 68.38 |
| 4.80 | 231,005 | 857.30 | 73.76 ic | 1.73 ic | 72.02 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 73.75 |
| 4.90 | 236,101 | 857.40 | 77.85 ic | 1.74 ic | 76.11 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 77.85 |
| 5.00 | 241,196 | 857.50 | 82.01 ic | 1.75 ic | 80.26 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 82.01 |
| 5.10 | 246,292 | 857.60 | 87.65 oc | 1.75 ic | 85.90 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 87.65 |
| 5.20 | 251,388 | 857.70 | 91.92 oc | 1.75 ic | 90.16 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 91.91 |
| 5.30 | 256,484 | 857.80 | 96.22 oc | 1.76 ic | 94.46 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 96.22 |
| 5.40 | 261,579 | 857.90 | 101.98 oc | 1.75 ic | 100.23 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 101.98 |
| 5.50 | 266,675 | 858.00 | 106.33 oc | 1.76 ic | 104.58 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 106.33 |
| 5.60 | 271,886 | 858.10 | 112.10 oc | 1.75 ic | 110.34 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 112.09 |
| 5.70 | 277,098 | 858.20 | 116.44 oc | 1.76 ic | 114.68 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 116.44 |
| 5.80 | 282,309 | 858.30 | 120.78 oc | 1.76 ic | 119.01 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 120.77 |
| 5.90 | 287,520 | 858.40 | 126.43 oc | 1.76 ic | 124.67 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 126.43 |
| 6.00 | 292,731 | 858.50 | 131.99 oc | 1.76 ic | 130.23 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 131.99 |
| 6.10 | 297,943 | 858.60 | 136.19 oc | 1.76 ic | 134.42 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 136.18 |
| 6.20 | 303,154 | 858.70 | 141.55 oc | 1.76 ic | 139.78 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 141.55 |
| 6.30 | 308,365 | 858.80 | 146.76 oc | 1.76 ic | 145.00 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 146.76 |
| 6.40 | 313,576 | 858.90 | 150.72 oc | 1.77 ic | 148.95 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 150.71 |
| 6.50 | 318,788 | 859.00 | 155.66 oc | 1.77 ic | 153.88 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 155.65 |
| 6.60 | 324,128 | 859.10 | 160.39 oc | 1.77 ic | 158.62 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 160.39 |
| 6.70 | 329,469 | 859.20 | 165.81 oc | 1.77 ic | 164.04 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 165.81 |
| 6.80 | 334,809 | 859.30 | 170.06 oc | 1.78 ic | 168.28 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 170.06 |
| 6.90 | 340,149 | 859.40 | 174.78 oc | 1.78 ic | 173.00 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 174.78 |
| 7.00 | 345,490 | 859.50 | 178.50 oc | 1.79 ic | 176.72 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 178.50 |
| 7.10 | 350,830 | 859.60 | 183.02 oc | 1.79 ic | 181.23 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 183.02 |
| 7.20 | 356,170 | 859.70 | 186.43 oc | 1.68 ic | 184.75 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 186.43 |
| 7.30 | 361,511 | 859.80 | 190.15 oc | 1.69 ic | 188.46 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 190.15 |
| 7.40 | 366,851 | 859.90 | 193.29 oc | 1.70 ic | 191.59 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 193.28 |
| 7.50 | 372,191 | 860.00 | 195.82 oc | 1.71 ic | 194.11 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 195.82 |
| 7.60 | 377,676 | 860.10 | 199.32 oc | 1.72 ic | 197.60 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 199.32 |
| 7.70 | 383,161 | 860.20 | 202.77 oc | 1.72 ic | 201.04 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 202.77 |
| 7.80 | 388,646 | 860.30 | 206.15 oc | 1.73 ic | 204.42 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 206.15 |
| 7.90 | 394,131 | 860.40 | 209.48 oc | 1.74 ic | 207.74 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 209.48 |
| 8.00 | 399,616 | 860.50 | 212.76 oc | 1.75 ic | 211.01 ic | --- | 0.00 | 0.00 | --- | --- | --- | --- | 212.76 |
| 8.10 | 405,101 | 860.60 | 215.67 oc | 1.75 ic | 212.23 ic | --- | 1.68 | 0.00 | --- | --- | --- | --- | 215.67 |
| 8.20 | 410,586 | 860.70 | 219.27 oc | 1.76 ic | 212.74 ic | --- | 4.76 | 0.00 | --- | --- | --- | --- | 219.26 |
| 8.30 | 416,071 | 860.80 | 223.34 oc | 1.76 ic | 212.84 ic | --- | 8.75 | 0.00 | --- | --- | --- | --- | 223.34 |
| 8.40 | 421,556 | 860.90 | 227.80 oc | 1.76 ic | 212.57 ic | --- | 13.47 | 0.00 | --- | --- | --- | --- | 227.79 |
| 8.50 | 427,041 | 861.00 | 232.57 oc | 1.75 ic | 211.98 ic | --- | 18.84 | 0.00 | --- | --- | --- | --- | 232.57 |
| 8.60 | 432,683 | 861.10 | 237.60 oc | 1.74 ic | 211.09 ic | --- | 24.76 | 0.00 | --- | --- | --- | --- | 237.60 |
| 8.70 | 438,324 | 861.20 | 242.86 oc | 1.73 ic | 209.92 ic | --- | 31.20 | 0.00 | --- | --- | --- | --- | 242.86 |
| 8.80 | 443,966 | 861.30 | 248.31 oc | 1.72 ic | 208.47 ic | --- | 38.12 | 0.00 | --- | --- | --- | --- | 248.31 |
| 8.90 | 449,608 | 861.40 | 253.94 oc | 1.71 ic | 206.74 ic | --- | 45.48 | 0.00 | --- | --- | --- | --- | 253.94 |
| 9.00 | 455,250 | 861.50 | 259.72 oc | 1.69 ic | 204.75 ic | --- | 53.27 | 0.00 | --- | --- | --- | --- | 259.72 |
| 9.10 | 460,891 | 861.60 | 265.63 oc | 1.67 ic | 202.49 ic | --- | 61.46 | 0.00 | --- | --- | --- | --- | 265.63 |
| 9.20 | 466,533 | 861.70 | 271.65 oc | 1.65 ic | 199.97 ic | --- | 70.02 | 0.00 | --- | --- | --- | --- | 271.64 |
| 9.30 | 472,175 | 861.80 | 277.76 oc | 1.63 ic | 197.17 ic | --- | 78.96 | 0.00 | --- | --- | --- | --- | 277.76 |
| 9.40 | 477,817 | 861.90 | 283.96 oc | 1.60 ic | 194.11 ic | --- | 88.24 | 0.00 | --- | --- | --- | --- | 283.95 |
| 9.50 | 483,459 | 862.00 | 290.23 oc | 1.58 ic | 190.77 ic | --- | 97.88 | 0.00 | --- | --- | --- | --- | 290.23 |
| 9.60 | 489,532 | 862.10 | 296.54 oc | 1.55 ic | 187.16 ic | --- | 107.83 | 0.00 | --- | --- | --- | --- | 296.54 |
| 9.70 | 495,605 | 862.20 | 302.90 oc | 1.51 ic | 183.28 ic | --- | 118.10 | 0.00 | --- | --- | --- | --- | 302.89 |

Continues on next page...

Walled Pond

Stage / Storage / Discharge Table

| Stage ft | Storage cuft | Elevation ft | Clv A cfs | Clv B cfs | Clv C cfs | PrfRsr cfs | Wr A cfs | Wr B cfs | Wr C cfs | Wr D cfs | Exfil cfs | User cfs | Total cfs |
|-------------|-----------------|-----------------|--------------|--------------|--------------|---------------|-------------|-------------|-------------|-------------|--------------|-------------|--------------|
| 9.80 | 501,679 | 862.30 | 309.26 oc | 1.48 ic | 179.12 ic | --- | 128.66 | 0.00 | --- | --- | --- | --- | 309.26 |
| 9.90 | 507,752 | 862.40 | 315.65 oc | 1.44 ic | 174.67 ic | --- | 139.53 | 0.00 | --- | --- | --- | --- | 315.64 |
| 10.00 | 513,825 | 862.50 | 322.03 oc | 1.40 ic | 169.93 ic | --- | 150.68 | 0.00 | --- | --- | --- | --- | 322.02 |
| 10.10 | 519,899 | 862.60 | 321.69 oc | 1.44 ic | 174.38 ic | --- | 124.66 ic | 2.29 | --- | --- | --- | --- | 302.77 |
| 10.20 | 525,972 | 862.70 | 321.37 oc | 1.48 ic | 178.68 ic | --- | 127.59 ic | 9.97 | --- | --- | --- | --- | 317.73 |
| 10.30 | 532,045 | 862.80 | 321.05 oc | 1.51 ic | 182.89 ic | --- | 130.46 ic | 20.66 | --- | --- | --- | --- | 335.52 |
| 10.40 | 538,119 | 862.90 | 321.21 oc | 1.54 ic | 186.40 ic | --- | 133.27 ic | 33.67 | --- | --- | --- | --- | 354.87 |
| 10.50 | 544,192 | 863.00 | 324.04 oc | 1.54 ic | 186.47 ic | --- | 136.02 ic | 48.67 | --- | --- | --- | --- | 372.71 |


...End

Cabelas Basin

Hydrograph Type = Reservoir
Storm Frequency = 50 yrs
Time Interval = 6 min

Peak Discharge = 102.19
Time to Peak = 12:10 hrs
Max Elevation = 871.41
Max Storage = 107,120 Ft³
Date = 6/2/2016

Notes:




Existing Pond

Hydrograph Type = Reservoir
Storm Frequency = 50 yrs
Time Interval = 6 min

Peak Discharge = 41.16
Time to Peak = 12:25 hrs

Max Elevation = 866.25
Max Storage = 42,017 Ft³
Date = 6/2/2016

Notes:




Primary Basin

Hydrograph Type = Reservoir
Storm Frequency = 50 yrs
Time Interval = 6 min

Peak Discharge = 173.75
Time to Peak = 12:25 hrs
Max Elevation = 859.71
Max Storage = 369,687 Ft³
Date = 3/16/2017

Notes: Detention Basin As-Built




Cabelas Basin

Hydrograph Type = Reservoir
Storm Frequency = 100 yrs
Time Interval = 6 min

Peak Discharge = 108.61
Time to Peak = 12:10 hrs
Max Elevation = 871.84
Max Storage = 114,387 Ft³
Date = 6/2/2016

Notes:




Existing Pond

Hydrograph Type = Reservoir
Storm Frequency = 100 yrs
Time Interval = 6 min

Peak Discharge = 42.67
Time to Peak = 12:25 hrs

Max Elevation = 866.53
Max Storage = 49,766 Ft³
Date = 6/2/2016


Notes:



Primary Basin

| | | | | |
|-----------------|---|-----------|------------------|-------------------------|
| Hydrograph Type | = | Reservoir | Peak Discharge = | 204.53 |
| Storm Frequency | = | 100 yrs | Time to Peak = | 12:25 hrs |
| Time Interval | = | 6 min | | |
| | | | Max Elevation = | 860.18 |
| | | | Max Storage = | 396,530 Ft ³ |
| | | | Date = | 3/16/2017 |

Notes: Detention As-Built



HY-8 Culvert Analysis Report

Crossing Discharge Data

Discharge Selection Method: Specify Minimum, Design, and Maximum Flow

Minimum Flow: 20.05 cfs

Design Flow: 208.15 cfs (100 yr Basin Outflow)

Maximum Flow: 329.42 cfs (100 yr Basin Inflow)

Table 1 - Summary of Culvert Flows at Crossing: Keefe Property

| Headwater Elevation (ft) | Total Discharge (cfs) | 4'x8' Box Discharge (cfs) | Roadway Discharge (cfs) | Iterations |
|--------------------------|-----------------------|---------------------------|-------------------------|-------------|
| 853.18 | 20.05 | 20.05 | 0.00 | 1 |
| 854.04 | 50.99 | 50.99 | 0.00 | 1 |
| 854.71 | 81.92 | 81.92 | 0.00 | 1 |
| 855.29 | 112.86 | 112.86 | 0.00 | 1 |
| 855.83 | 143.80 | 143.80 | 0.00 | 1 |
| 856.36 | 174.74 | 174.74 | 0.00 | 1 |
| 856.91 | 205.67 | 205.67 | 0.00 | 1 |
| 857.02 | 208.15 | 208.15 | 0.00 | 1 |
| 858.24 | 267.55 | 267.55 | 0.00 | 1 |
| 859.40 | 298.48 | 298.48 | 0.00 | 1 |
| 860.64 | 329.42 | 329.42 | 0.00 | 1 |
| 862.54 | 373.32 | 373.32 | 0.00 | Overtopping |

Rating Curve Plot for Crossing: Keefe Property




Table 2 - Culvert Summary Table: 4'x8' Box


| Total Discharge (cfs) | Culvert Discharge (cfs) | Headwater Elevation (ft) | Inlet Control Depth (ft) | Outlet Control Depth (ft) | Flow Type | Normal Depth (ft) | Critical Depth (ft) | Outlet Depth (ft) | Tailwater Depth (ft) | Outlet Velocity (ft/s) | Tailwater Velocity (ft/s) |
|-----------------------|-------------------------|--------------------------|--------------------------|---------------------------|-----------|-------------------|---------------------|-------------------|----------------------|------------------------|---------------------------|
| 20.05 | 20.05 | 853.18 | 0.993 | 0.0* | 1-JS1t | 0.565 | 0.580 | 0.650 | 0.650 | 3.853 | 7.706 |
| 50.99 | 50.99 | 854.04 | 1.850 | 0.0* | 1-JS1t | 1.055 | 1.081 | 1.233 | 1.233 | 5.169 | 10.338 |
| 81.92 | 81.92 | 854.71 | 2.519 | 0.643 | 1-JS1t | 1.448 | 1.482 | 1.737 | 1.737 | 5.897 | 11.794 |
| 112.86 | 112.86 | 855.29 | 3.103 | 1.370 | 1-JS1t | 1.799 | 1.835 | 2.207 | 2.207 | 6.393 | 12.786 |
| 143.80 | 143.80 | 855.83 | 3.644 | 2.160 | 1-S2n | 2.126 | 2.157 | 2.126 | 2.658 | 8.456 | 13.524 |
| 174.74 | 174.74 | 856.36 | 4.174 | 3.019 | 5-S2n | 2.437 | 2.456 | 2.437 | 3.098 | 8.962 | 14.103 |
| 205.67 | 205.67 | 856.91 | 4.718 | 3.952 | 5-S2n | 2.737 | 2.738 | 2.737 | 3.529 | 9.392 | 14.572 |
| 208.15 | 208.15 | 857.02 | 4.762 | 4.832 | 7-M1t | 2.761 | 2.760 | 3.563 | 3.563 | 7.303 | 14.606 |
| 267.55 | 267.55 | 858.24 | 5.924 | 6.046 | 4-FFf | 3.313 | 3.263 | 4.000 | 4.374 | 8.361 | 15.293 |
| 298.48 | 298.48 | 859.40 | 6.616 | 7.209 | 4-FFf | 3.592 | 3.510 | 4.000 | 4.790 | 9.328 | 15.578 |
| 329.42 | 329.42 | 860.64 | 7.379 | 8.451 | 4-FFf | 4.000 | 3.748 | 4.000 | 5.204 | 10.294 | 15.826 |

* Full Flow Headwater elevation is below inlet invert.

Straight Culvert
Inlet Elevation (invert): 852.19 ft, Outlet Elevation (invert): 850.81 ft
Culvert Length: 461.00 ft, Culvert Slope: 0.0030

Water Surface Profile Plot for Culvert: 4'x8' Box

Crossing - Keefe Property, Design Discharge - 208.2 cfs
Culvert - 4'x8' Box, Culvert Discharge - 208.2 cfs



Site Data - 4'x8' Box

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 852.19 ft

Outlet Station: 461.00 ft

Outlet Elevation: 850.81 ft

Number of Barrels: 1

Culvert Data Summary - 4'x8' Box

Barrel Shape: Concrete Box

Barrel Span: 8.00 ft

Barrel Rise: 4.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge (90°) Headwall

Inlet Depression: NONE

Tailwater Channel Data - Keefe Property

Tailwater Channel Option: Rectangular Channel

Bottom Width: 4.00 ft

Channel Slope: 0.0100

Channel Manning's n: 0.0120

Channel Invert Elevation: 850.81 ft

Roadway Data for Crossing: Keefe Property

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 60.00 ft


Crest Elevation: 862.54 ft




Roadway Surface: Paved

Roadway Top Width: 380.00 ft

X.

TRASH RACK: STORMRAX, PEAK SERIES OR APPROVED EQUAL.
CONTRACTOR SHALL PROVIDE SHOP DRAWING SUBMITTAL
FOR REVIEW & APPROVAL BY OWNER PRIOR TO ORDERING MATERIAL.





THIS DOCUMENT AND ALL RELATED DETAIL DRAWINGS, SPECIFICATIONS AND ELECTRONIC MEDIA PREPARED OR FORWARDED BY BAYER BECKER (BB) ARE INSTRUMENTS OF BB'S PROFESSIONAL SERVICE AND IF THE EXCLUSIVE PROPERTY OF BB. NO DISCLOSURE, REPRODUCTION OR IN PART MAY BE MADE WITHOUT WRITTEN PERMISSION OF BB. AND IS DONE SO AT USER'S SOLE RISK. COPYRIGHT - ALL RIGHTS RESERVED.

| Item | Revision Description | Date | Drawn | Chk |
|------|----------------------------------|----------|-------|-----|
| 1 | REISSUED | 07-29-16 | AJW | JSD |
| 2 | FINAL DEVELOPMENT PLAN SUBMITTAL | 08-15-16 | AJW | JSD |
| 3 | BULLETIN #2 | 10-14-16 | AJW | JSD |
| 4 | DETENTION AS-BUILT | 03-16-17 | AJW | JSD |

KEEFE PROPERTY SP-PUD TRACTS 283
ROADWAY AND MISC SITE FDP
LIBERTY WAY & TYLERS PLACE BLVD
SECTION 18, TOWN 3, RANGE 2
WEST CHESTER TOWNSHIP
BUTLER COUNTY, OHIO

UTILITY PROFILES

Drawing: 15M053-000 UTILITY
Drawn by: AJW
Checked by: JSD
Issue Date: 06-17-16

C4.3

bayer
becker
www.bayerbecker.com
6900 Tyersville Road, Suite A
Mason, OH 45040 - 513.336.6600