

# Senior Residential Development - Traffic Impact Study


## Butler County, Ohio

**Mason**

7288 Central Parke  
Mason, OH 45040  
513.771.8828  
FAX: 513.771.0707

**Dayton**

77 W. Elmwood Dr.  
Suite 200  
Dayton, OH 45459  
937.435.8828  
FAX: 937.435.8833




**Prepared for:**  
Infrastructure & Development  
Engineering, Inc.  
2451 Crowne Point Drive  
Cincinnati, OH 45241

**Prepared by:**  
TEC Engineering, Inc.  
7288 Central Parke  
Mason, Ohio 45040

TEC PN – 20270-002

# Traffic Impact Study

## Hamilton Mason Road Development Butler County, Ohio



### Prepared For:

**Infrastructure & Development Engineering, Inc.**  
2451 Crowne Point Drive  
Cincinnati, OH 45241

### Prepared By:



7288 Central Parke Blvd.  
Mason, Ohio 45040

January 2021

Received via email on  
01/05/2021

## Table of Contents

|  |    |
|--|----|
| Executive Summary.....                 | 3  |
| 1. Introduction .....                  | 4  |
| General Layout.....                    | 4  |
| 2. Background Traffic .....            | 5  |
| 3. Generated Traffic.....              | 5  |
| 4. Trip Distribution.....              | 5  |
| 5. Capacity Analysis.....              | 8  |
| Capacity Analysis.....                 | 8  |
| 6. Warrants .....                      | 9  |
| Turn Lane Warrants .....               | 9  |
| 7. Sight Distance Study.....           | 12 |
| 8. Conclusions & Recommendations ..... | 14 |

## Executive Summary

### Purpose and Objectives

TEC Engineering, Inc. was retained by Infrastructure & Development Engineering Inc. to conduct a Traffic Impact Study for a proposed development on the south side of Hamilton Mason Rd., east of Maud Hughes Rd. in West Chester Township in Butler County, Ohio. The objective of this report is to document existing traffic conditions and patterns and evaluate the potential impacts of the proposed development on the surrounding transportation network.

### Existing Conditions

Hamilton Mason Rd. is a 2-lane road, with a 45 MPH speed limit, that runs east and west along the northern edge of the proposed development.

### Proposed Development

### Traffic Analyses

TEC conducted Turning Movement Counts in February of 2020, a 2% growth rate was applied to these volumes to create the 2022 and 2042 volumes. Trips were generated using the *Institute of Transportation Engineers (ITE) Trip Generation Handbook*.

Using projected volumes and generated trips, a turn lane warrant was performed for the access points into the site. The following scenarios were analyzed:

- 2022 Build (AM & PM)
- 2042 Build (AM & PM)


### Conclusions and Recommendations

As a result of the study, TEC found that the proposed development did not produce a negative impact on the existing roadway network. There are no improvements required to the existing roadway. Turn lane warrants were not met, and given the small number of trips generated, capacity will not be an issue. The site access should be on the far west end of the site. Care should be taken when designing the profile of the development access to maximize sight distance for drivers exiting the development as well as drivers along Hamilton Mason Road.

## 1. Introduction

TEC Engineering, Inc. was retained by Infrastructure & Development Engineering Inc. to conduct a Traffic Impact Study for a proposed development on the south side of Hamilton Mason Rd. There is one access point proposed on the south side of Hamilton Mason Rd.

*Figure 1.1: Location Map*



### General Layout

Hamilton Mason Rd. is a 2-lane road that is a Major Collector. Hamilton Mason Rd. has a speed limit of 45 MPH and carries approximately 6,326 vehicles per day. Maud Hughes Rd. is located to the west of the development.


There was one intersection in the study that was analyzed for traffic impact. Using projected background traffic and generated trips, a turn lane warrant was conducted for the two intersections. The intersections are listed below:

- Hamilton Mason Road & Access

## 2. Background Traffic

TEC conducted Turning Movement Counts at Hamilton Mason Road & Maud Hughes in February of 2020. The peak hours were found to be 7:00-8:00 AM and 5:00-6:00 PM. Due to the recent changes in traffic due to Covid-19, the volumes for this report were calculated based on the turning movements from this adjacent intersection. The 2020 Volume is shown in Figure 2.1.

**Figure 2.1: 2020 Traffic Counts**



A straight-line growth rate of 2.0% per year was applied to the existing traffic volume data collected to account for traffic volume growth in the area while the site is being developed. The Existing, No Build and Build volumes are shown in *Section 4: Trip Distribution*. Existing volumes can be found in *Appendix B*.

## 3. Generated Traffic

Trips for Senior Adult Housing were generated based on details provided by the developer in conjunction with the *Institute of Transportation Engineers (ITE) Trip Generation Handbook*. This Handbook is the most widely accepted publication for projecting traffic volumes. Volume projections are based on specifics of the site usage. The trips generated by the proposed development site were projected using the trip generation rates and equations provided in the handbook. The dwellings will be attached units in groups of 2-6 units per building. Land use 252-Senior Adult Housing-Attached was found to best represent the development. The development size of the study locations for the “Attached” land use also better matches the development size of this development. The “Attached” study locations have an average of 148 units, while the LU-251 “Detached” land use study locations have an average of 582 dwellings, so they are much larger developments overall.

**Table 3.1: Trip Generation and Enter/Exit Distributions (Senior Adult Housing-Attached)**

| Land Use                      | Units     | Quantity | Peak | Generation Rate | Total Trips | Enter % | Exit % | Entering Trips | Exiting Trips |
|-------------------------------|-----------|----------|------|-----------------|-------------|---------|--------|----------------|---------------|
| Senior Adult Housing-Attached | Dwellings | 120      | AM   | 0.2x-0.18       | 23          | 35%     | 65%    | 8              | 15            |
|                               |           |          | PM   | 0.25x+2.26      | 33          | 55%     | 45%    | 18             | 15            |

## 4. Trip Distribution

Before newly generated trips could be distributed throughout the network, existing 2020 traffic was projected based on 2.0% growth rate to form the “No Build” base for analysis. The projected 2022 traffic can be seen in *Figure 4.1*. The 2042 volumes are in *Figures 4.2*.

**Figure 4.1: 2022 No Build Traffic**




**Figure 4.2: 2042 No Build Traffic**




Before modeling all “build” traffic volumes, new trips were distributed based on existing traffic patterns. After determining distributions for new traffic. 2022 Build Volumes can be found in *Figures 4.5* and lastly 2032 Build Volumes can be found in *Figures 4.6*.


**Figure 4.3: Trip Distribution %**




**Figure 4.4: New Trips**



**Figure 4.5: 2022 Build Volumes**



**Figure 4.5: 2042 Build Volumes**



## 5. Capacity Analysis

To determine any improvements necessary to accommodate the traffic generated by the proposed development, the following scenarios were compared and analyzed for all scenarios:

- 2022 AM/PM Build
- 2042 AM/PM Build

### Capacity Analysis

TEC used the software program *HCS 7* to evaluate each scenario individually. The capacity analysis was performed using the existing conditions for both the “Build” and “No Build” scenarios. The Level of Service (LOS) for the intersection is directly related to the average total delay per vehicle. The total delay is the sum of control delay and queue delay. Control delay is the component of delay caused by the downstream control device and is calculated using the Percentile Delay Method. Queue delay is an analysis of the effects of queues and blocking on short links and short turning bays. LOS is defined in terms of delay and is a measure of driver discomfort and intersection performance with respect to vehicular capacity and quality of service provided to road users. Delay refers to total average stopped delay experienced by motorists at the referenced intersection. The level of service is classified into six different levels, ranging from A to F, and is detailed in *Table 5.1* for unsignalized intersections. Capacity analysis reports from *HCS 7* can be found in *Appendix C*.

**Table 5.1: Unsignalized Intersection Level of Service Classifications**

| Level of Service | Description                              | Delay                     |
|------------------|--|---------------------------|
| A                | Very low delay                           | <10 seconds per vehicle   |
| B                | Good progression                         | 10-15 seconds per vehicle |
| C                | Limit of acceptable delay                | 15-25 seconds per vehicle |
| D                | Start of traffic breakdown               | 25-35 seconds per vehicle |
| E                | High delay                               | 35-50 seconds per vehicle |
| F                | Congested conditions, unacceptable delay | >50 seconds per vehicle   |

All capacity analysis results can be found in *Tables 5.2*. All intersections were analyzed using “No Build” conditions and “Build” traffic volumes with existing roadway geometries.

**Table 5.2: Delay & LOS**

| Hamilton-Mason Rd. & Access |          |       |           |   |            |   |
|-----------------------------|----------|-------|-----------|---|------------|---|
| Peak                        | Scenario |       | Westbound |   | Northbound |   |
| AM                          | 2022     | Build | 0.4       | A | 10.8       | B |
|                             | 2042     | Build | 0.3       | A | 12.2       | B |
| PM                          | 2022     | Build | 0.3       | A | 12.0       | B |
|                             | 2042     | Build | 0.3       | A | 14.5       | B |

## 6. Warrants

---

### Turn Lane Warrants

A turn lane warrant was performed to determine the need for a right turn lane or left turn lane on Hamilton Mason Road at the proposed site. The right turn warrant is based on the advancing volumes and the right turning volume. The left turn warrant is based on the advancing volume, the opposing volume, and the percentage of the advancing volume that is turning left. *Table 6.1* displays the results of the turn lane warrant. The warrant graphs are shown in figures 6.1 and 6.2. As a result of the turn lane warrant study, no turn lanes are required.


**Table 6.1 Turn Lane Warrants**

| Warrant            | Warrants? |
|--------------------|-----------|
| WB Left Turn Lane  | No        |
| EB Right Turn Lane | No        |

Figure 6.1 WB Left Turn Lane

**FIGURE B: 2-LANE HIGHWAY LEFT TURN LANE WARRANT  
 (>40 MPH OR 70 KPH POSTED SPEED)**

| Location | Advancing Traffic |      |       |       |        | Opposing Traffic |      |       |       |
|----------|-------------------|------|-------|-------|--------|------------------|------|-------|-------|
|          | Left              | Thru | Right | Total | % Left | Left             | Thru | Right | Total |
| 2022 AM  | 6                 | 139  | 0     | 145   | 4.1%   | 0                | 315  | 5     | 320   |
| 2022 PM  | 11                | 401  | 0     | 412   | 2.7%   | 0                | 265  | 15    | 280   |
| 2042 AM  | 6                 | 195  | 0     | 201   | 3.0%   | 0                | 441  | 5     | 446   |
| 2042 PM  | 11                | 561  | 0     | 572   | 1.9%   | 0                | 371  | 15    | 386   |
|          | 0                 | 0    | 0     | 0     |        | 0                | 0    | 0     | 0     |
|          | 0                 | 0    | 0     | 0     |        | 0                | 0    | 0     | 0     |
|          | 0                 | 0    | 0     | 0     |        | 0                | 0    | 0     | 0     |




Is Left Turn Lane Warrant met? **No**

**Figure 6.2 EB Right Turn Lane**

**2-LANE HIGHWAY RIGHT TURN LANE WARRANT  
 >40 MPH OR 70 KPH POSTED SPEED**

| Location | Right Turn Volume |      | Advancing Traffic |       |       |
|----------|-------------------|------|-------------------|-------|-------|
|          | Right             | Left | Thru              | Right | Total |
| 2022 AM  | 2                 | 0    | 315               | 2     | 317   |
| 2022 PM  | 7                 | 0    | 265               | 7     | 272   |
| 2042 AM  | 2                 | 0    | 441               | 2     | 443   |
| 2042 PM  | 7                 | 0    | 371               | 7     | 378   |
|          | 0                 | 0    | 0                 | 0     | 0     |
|          | 0                 | 0    | 0                 | 0     | 0     |
|          | 0                 | 0    | 0                 | 0     | 0     |



\*Includes Right Turns

Is Right Turn Lane Warrant met?  NO

## 7. Sight Distance Study

A sight distance study was performed at the proposed entrances to the site. TEC evaluated site distance at several points along Hamilton Mason Road. TEC performed a sight distance study to determine the intersection sight distance (ISD) at several points along the property also comparing these values to the stopping sight distance (SSD). Intersection sight was measured from 10-15' from the edge of pavement. This was not possible at some locations due to the brush. Since the brush will be removed with the development, sight lines blocked by brush were not excluded from the study. In these locations, where the brush or fences made this impossible to get the full 15' from the pavement, engineering judgement was used to determine if the sight distance would be the same from the point further back. The original study was done using the intersection sight triangle method with a 4.25' height of object and 3.5' height of eye.

To clarify: The original study was not redone with correct 3.5' height of eye.

As seen in the figure below, points A, B and C were provided by the client. Point D was determined to be the point on the east half of the site with the optimal sight distance. This location does not meet intersection sight distance in either direction.

Figure 7.1 Sight Distance Study Points



Table 7.1 AASHTO Required Sight Distance

| Design Speed | ISD  | SSD  |
|--------------|------|------|
| 35 mph       | 390' | 250' |
| 40 mph       | 445' | 305' |
| 45 mph       | 500' | 360' |

**Table 7.2 Measured Intersection Sight Distance**

| Location  | Looking Left (to the west) | Looking Right (to the east) | Meets ISD 45mph |
|---|----------------------------|-----------------------------|-----------------|
| A - Preferred Driveway Location                   | 166'                       | 386'                        | No              |
| B - Preferred Driveway further East               | 212'                       | 353'                        | No              |
| C - Secondary Access Point                        | 500'+                      | 430'                        | No              |
| D - Optimal Sight Distance 99' West of Location A | 374'                       | 336'                        | No              |

Of the measured points, Point C on the west end of the site has the best sight distance.

TEC also reviewed stopping sight distance at Locations A and B. This is the distance along Hamilton Mason Road where a “car” exiting the access is visible to a driver along Hamilton Mason Road or a vehicle waiting to left into the development from Hamilton Mason Road.


**Table 7.3 Measured Stopping Sight Distance**

| Location                            | From the West | From the East | Meets SSD 45mph |
|-------------------------------------|---------------|---------------|-----------------|
| A - Preferred Driveway Location     | 298'          | 290'          | No/No           |
| B - Preferred Driveway further East | 305'          | 360'          | No/Yes          |

The table above shows the stopping sight distance to see a 2' object, or the height of a taillight on a typical vehicle, in the road.

**Since the original access locations did not meet the 500' Intersection Sight Distance additional study was needed.** IDE determined another possible driveway location shown as shown in Figure 7.2. This study was completed with a 3.5' height of object to meet ODOT L&D requirements.

**Figure 7.2 Secondary Sight Distance Study Points**



**Table 7.4 Measured Intersection Sight Distance**

| Please provide a distance reference of preferred drive at "far west end". |  | Looking Left (to the west) | Looking Right (to the east) | Meets ISD 45mph |
|---|--|----------------------------|-----------------------------|-----------------|
| Location  |  |                            |                             |                 |
| E – far West Driveway Location  |  | 573'                       | 532'                        | YES             |

Stopping sight distance was also confirmed for the new location. Stopping sight distance was greater than 400' in both directions.

**Based on this study, the new location on the far west end of the site is the preferred location for the access.**

## **8. Conclusions & Recommendations**

---


As a result of the study, TEC found that the proposed development did not produce a negative impact on the existing roadway network. There are no improvements required to the existing roadway. Turn lane warrants were not met, and given the small number of trips generated, capacity will not be an issue. The access should be located on the far west end of the site. **Care should be taken when designing profile of the development access to maximize sight distance for drivers exiting the development as well as drivers along Hamilton Mason Road.**

The TIS is approved with conditions:


1. Prior to CO, submit a more detailed sight distance study with field survey using actual design of proposed driveway to confirm adequate sight distance is achieved.

# Appendix


# HCS7 Two-Way Stop-Control Report

| General Information  |               |   |   | Site Information                           |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|---------------|---|---|--|---------------------------|---|------------|--------------------------------|---|------------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Analyst  |               |   |   | Intersection                               | Hamilton Mason Rd & Acces |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Agency/Co.   |               |   |   | Jurisdiction                               |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Date Performed   | 11/17/2020    |   |   | East/West Street                           | Hamilton Mason Rd.        |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Analysis Year  | 2022          |   |   | North/South Street                         | Access                    |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Time Analyzed  | AM BUILD 2022 |   |   | Peak Hour Factor                           | 0.92                      |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Intersection Orientation   | East-West     |   |   | Analysis Time Period (hrs)                 | 0.25                      |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Project Description  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Lanes  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| <br>Major Street: East-West |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Vehicle Volumes and Adjustments  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach   | Eastbound     |   |   | Westbound                                  |                           |   | Northbound |                                |   | Southbound |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Movement   | U             | L | T | R  | U                         | L | T          | R                              | U | L          | T |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Priority   | 1U            | 1 | 2 | 3  | 4U                        | 4 | 5          | 6                              | 7 | 8          | 9 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Number of Lanes  | 0             | 0 | 1 | 0  | 0                         | 0 | 1          | 0                              | 0 | 1          | 0 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Configuration  |               |   |   | TR   |                           |   |            | LT                             |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Volume (veh/h)   |               |   |   | 315  |                           |   |            | 6                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Heavy Vehicles (%)   |               |   |   |  |                           |   |            | 3                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Proportion Time Blocked  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Grade (%)  |               |   |   |  |                           |   |            | 0                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Right Turn Channelized   |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Median Type   Storage  |               |   |   | Undivided                                  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical and Follow-up Headways  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Critical Headway (sec)  |               |   |   |  |                           |   |            | 4.1                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical Headway (sec)   |               |   |   |  |                           |   |            | 4.13                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Follow-Up Headway (sec)   |               |   |   |  |                           |   |            | 2.2                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Follow-Up Headway (sec)  |               |   |   |  |                           |   |            | 2.23                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Delay, Queue Length, and Level of Service  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Flow Rate, v (veh/h)   |               |   |   |  |                           |   |            | 7                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Capacity, c (veh/h)  |               |   |   |  |                           |   |            | 1209                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| v/c Ratio  |               |   |   |  |                           |   |            | 0.01                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 95% Queue Length, Q <sub>95</sub> (veh)  |               |   |   |  |                           |   |            | 0.0                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Control Delay (s/veh)  |               |   |   |  |                           |   |            | 8.0                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Level of Service (LOS)   |               |   |   |  |                           |   |            | A                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach Delay (s/veh)   |               |   |   |  |                           |   |            | 0.4                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach LOS   |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Copyright © 2021 University of Florida. All Rights Reserved.   |               |   |   | HCS7 TWSC Version 7.9<br>2022 AM Build.xtw |                           |   |            | Generated: 1/4/2021 8:14:55 AM |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |


# HCS7 Two-Way Stop-Control Report

| General Information   |               |   |   | Site Information           |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---|---------------|---|---|----------------------------|---------------------------|---|------------|-----|------|------------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Analyst   |               |   |   | Intersection               | Hamilton Mason Rd & Acces |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Agency/Co.  |               |   |   | Jurisdiction               |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Date Performed  | 11/17/2020    |   |   | East/West Street           | Hamilton Mason Rd.        |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Analysis Year   | 2022          |   |   | North/South Street         | Access                    |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Time Analyzed   | PM BUILD 2022 |   |   | Peak Hour Factor           | 0.92                      |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Intersection Orientation  | East-West     |   |   | Analysis Time Period (hrs) | 0.25                      |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Project Description   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Lanes   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Vehicle Volumes and Adjustments   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach  | Eastbound     |   |   | Westbound                  |                           |   | Northbound |     |      | Southbound |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Movement  | U             | L | T | R                          | U                         | L | T          | R   | U    | L          | T |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Priority  | 1U            | 1 | 2 | 3                          | 4U                        | 4 | 5          | 6   | 7    | 8          | 9 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Number of Lanes   | 0             | 0 | 1 | 0                          | 0                         | 0 | 1          | 0   | 0    | 1          | 0 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Configuration   |               |   |   | TR                         |                           |   |            | LT  |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Volume (veh/h)  | 265           |   |   | 7                          | 11                        |   |            | 401 | 6    |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Heavy Vehicles (%)  |               |   |   |                            | 3                         |   |            |     | 3    |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Proportion Time Blocked   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Grade (%)   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Right Turn Channelized  |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Median Type   Storage   | Undivided     |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical and Follow-up Headways   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Critical Headway (sec)   |               |   |   |                            | 4.1                       |   |            |     | 7.1  |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical Headway (sec)  |               |   |   |                            | 4.13                      |   |            |     | 6.43 |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Follow-Up Headway (sec)  |               |   |   |                            | 2.2                       |   |            |     | 3.5  |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Follow-Up Headway (sec)   |               |   |   |                            | 2.23                      |   |            |     | 3.53 |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Delay, Queue Length, and Level of Service   |               |   |   |                            |                           |   |            |     |      |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Flow Rate, v (veh/h)  |               |   |   |                            | 12                        |   |            |     | 16   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Capacity, c (veh/h)   |               |   |   |                            | 1260                      |   |            |     | 532  |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| v/c Ratio   |               |   |   |                            | 0.01                      |   |            |     | 0.03 |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 95% Queue Length, Q <sub>95</sub> (veh)   |               |   |   |                            | 0.0                       |   |            |     | 0.1  |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Control Delay (s/veh)   |               |   |   |                            | 7.9                       |   |            |     | 12.0 |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Level of Service (LOS)  |               |   |   |                            | A                         |   |            |     | B    |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach Delay (s/veh)  |               |   |   |                            | 0.3                       |   |            |     | 12.0 |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach LOS  |               |   |   |                            |                           |   |            |     | B    |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

# HCS7 Two-Way Stop-Control Report

| General Information  |               |   |   | Site Information                           |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|---------------|---|---|--|---------------------------|---|------------|--------------------------------|---|------------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Analyst  |               |   |   | Intersection                               | Hamilton Mason Rd & Acces |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Agency/Co.   |               |   |   | Jurisdiction                               |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Date Performed   | 11/17/2020    |   |   | East/West Street                           | Hamilton Mason Rd.        |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Analysis Year  | 2042          |   |   | North/South Street                         | Access                    |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Time Analyzed  | AM BUILD 2042 |   |   | Peak Hour Factor                           | 0.92                      |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Intersection Orientation   | East-West     |   |   | Analysis Time Period (hrs)                 | 0.25                      |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Project Description  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Lanes  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| <br>Major Street: East-West |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Vehicle Volumes and Adjustments  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach   | Eastbound     |   |   | Westbound                                  |                           |   | Northbound |                                |   | Southbound |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Movement   | U             | L | T | R  | U                         | L | T          | R                              | U | L          | T |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Priority   | 1U            | 1 | 2 | 3  | 4U                        | 4 | 5          | 6                              | 7 | 8          | 9 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Number of Lanes  | 0             | 0 | 1 | 0  | 0                         | 0 | 1          | 0                              | 0 | 1          | 0 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Configuration  |               |   |   | TR   |                           |   |            | LT                             |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Volume (veh/h)   |               |   |   | 441  |                           |   |            | 6                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Heavy Vehicles (%)   |               |   |   |  |                           |   |            | 195                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Proportion Time Blocked  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Grade (%)  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Right Turn Channelized   |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Median Type   Storage  |               |   |   | Undivided                                  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical and Follow-up Headways  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Critical Headway (sec)  |               |   |   |  |                           |   |            | 4.1                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical Headway (sec)   |               |   |   |  |                           |   |            | 4.13                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Follow-Up Headway (sec)   |               |   |   |  |                           |   |            | 2.2                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Follow-Up Headway (sec)  |               |   |   |  |                           |   |            | 2.23                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Delay, Queue Length, and Level of Service  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Flow Rate, v (veh/h)   |               |   |   |  |                           |   |            | 7                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Capacity, c (veh/h)  |               |   |   |  |                           |   |            | 1076                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| v/c Ratio  |               |   |   |  |                           |   |            | 0.01                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 95% Queue Length, Q <sub>95</sub> (veh)  |               |   |   |  |                           |   |            | 0.0                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Control Delay (s/veh)  |               |   |   |  |                           |   |            | 8.4                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Level of Service (LOS)   |               |   |   |  |                           |   |            | A                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach Delay (s/veh)   |               |   |   |  |                           |   |            | 0.3                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach LOS   |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Copyright © 2021 University of Florida. All Rights Reserved.   |               |   |   | HCS7 TWSC Version 7.9<br>2042 AM Build.xtw |                           |   |            | Generated: 1/4/2021 8:16:00 AM |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

# HCS7 Two-Way Stop-Control Report

| General Information  |               |   |   | Site Information                           |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|---------------|---|---|--|---------------------------|---|------------|--------------------------------|---|------------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Analyst  |               |   |   | Intersection                               | Hamilton Mason Rd & Acces |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Agency/Co.   |               |   |   | Jurisdiction                               |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Date Performed   | 11/17/2020    |   |   | East/West Street                           | Hamilton Mason Rd.        |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Analysis Year  | 2042          |   |   | North/South Street                         | Access                    |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Time Analyzed  | PM BUILD 2042 |   |   | Peak Hour Factor                           | 0.92                      |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Intersection Orientation   | East-West     |   |   | Analysis Time Period (hrs)                 | 0.25                      |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Project Description  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Lanes  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  <p>Major Street: East-West</p> |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Vehicle Volumes and Adjustments  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach   | Eastbound     |   |   | Westbound                                  |                           |   | Northbound |                                |   | Southbound |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Movement   | U             | L | T | R  | U                         | L | T          | R                              | U | L          | T |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Priority   | 1U            | 1 | 2 | 3  | 4U                        | 4 | 5          | 6                              | 7 | 8          | 9 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Number of Lanes  | 0             | 0 | 1 | 0  | 0                         | 0 | 1          | 0                              | 0 | 1          | 0 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Configuration  |               |   |   | TR   |                           |   |            | LT                             |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Volume (veh/h)   |               |   |   | 371  |                           |   |            | 11                             |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Heavy Vehicles (%)   |               |   |   |  |                           |   |            | 561                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Proportion Time Blocked  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Percent Grade (%)  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Right Turn Channelized   |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Median Type   Storage  |               |   |   | Undivided                                  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical and Follow-up Headways  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Critical Headway (sec)  |               |   |   |  |                           |   |            | 4.1                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Critical Headway (sec)   |               |   |   |  |                           |   |            | 4.13                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Base Follow-Up Headway (sec)   |               |   |   |  |                           |   |            | 2.2                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Follow-Up Headway (sec)  |               |   |   |  |                           |   |            | 2.23                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Delay, Queue Length, and Level of Service  |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Flow Rate, v (veh/h)   |               |   |   |  |                           |   |            | 12                             |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Capacity, c (veh/h)  |               |   |   |  |                           |   |            | 1143                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| v/c Ratio  |               |   |   |  |                           |   |            | 0.01                           |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 95% Queue Length, Q <sub>95</sub> (veh)  |               |   |   |  |                           |   |            | 0.0                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Control Delay (s/veh)  |               |   |   |  |                           |   |            | 8.2                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Level of Service (LOS)   |               |   |   |  |                           |   |            | A                              |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach Delay (s/veh)   |               |   |   |  |                           |   |            | 0.3                            |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Approach LOS   |               |   |   |  |                           |   |            |                                |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Copyright © 2021 University of Florida. All Rights Reserved.   |               |   |   | HCS7 TWSC Version 7.9<br>2042 PM Build.xtw |                           |   |            | Generated: 1/4/2021 8:16:29 AM |   |            |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |